

[illegible]

```
LL      NN      NN      KK      KK      SSSSSSSS      YY      YY      MM      MM      TTTTTTTTTT      88888888      LL
LL      NN      NN      KK      KK      SSSSSSSS      YY      YY      MM      MM      TTTTTTTTTT      88888888      LL
LL      NN      NN      KK      KK      SS      YY      YY      MM      MM      TT      88      88      LL
LL      NN      NN      KK      KK      SS      YY      YY      MM      MM      TT      88      88      LL
LL      NNNN      NN      KK      KK      SS      YY      YY      MM      MM      TT      88      88      LL
LL      NNNN      NN      KK      KK      SS      YY      YY      MM      MM      TT      88      88      LL
LL      NN      NN      KKKKKK      KK      SSSSSS      YY      YY      MM      MM      TT      88888888      LL
LL      NN      NN      KKKKKK      KK      SSSSSS      YY      YY      MM      MM      TT      88888888      LL
LL      NN      NNNN      KK      KK      SS      YY      YY      MM      MM      TT      88      88      LL
LL      NN      NNNN      KK      KK      SS      YY      YY      MM      MM      TT      88      88      LL
LL      NN      NN      KK      KK      SS      YY      YY      MM      MM      TT      88      88      LL
LL      NN      NN      KK      KK      SSSSSSSS      YY      YY      MM      MM      TT      88      88      LL
LLLLLLLLLLLL      NN      NN      KK      KK      SSSSSSSS      YY      MM      MM      TT      88888888      LLLLLLLLLL      ....
LLLLLLLLLLLL      NN      NN      KK      KK      SSSSSSSS      YY      MM      MM      TT      88888888      LLLLLLLLLL      ....
```

```
LL      IIIIII      SSSSSSSS
LL      IIIIII      SSSSSSSS
LL      II      SS
LL      II      SS
LL      II      SS
LL      II      SSSSSS
LL      II      SSSSSS
LL      II      SS
LL      II      SS
LL      II      SS
LL      II      SS
LLLLLLLLLLLL      IIIIII      SSSSSSSS
LLLLLLLLLLLL      IIIIII      SSSSSS
```

```

1 0001 0 MODULE LNK_SYMSEIRINS (IDENT='V04-000',
2 0002 0 ADDRESSING_MODE (EXTERNAL=GENERAL,
3 0003 0 NONEXTERNAL=LONG_RELATIVE)
4 0004 0 ) =
5 0005 0
6 0006 1 BEGIN
7 0007 1
8 0008 1
9 0009 1 *****
10 0010 1 *
11 0011 1 * COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
12 0012 1 * DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
13 0013 1 * ALL RIGHTS RESERVED.
14 0014 1 *
15 0015 1 * THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
16 0016 1 * ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
17 0017 1 * INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
18 0018 1 * COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
19 0019 1 * OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
20 0020 1 * TRANSFERRED.
21 0021 1 *
22 0022 1 * THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
23 0023 1 * AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
24 0024 1 * CORPORATION.
25 0025 1 *
26 0026 1 * DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
27 0027 1 * SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.
28 0028 1 *
29 0029 1 *
30 0030 1 *****
31 0031 1
32 0032 1
33 0033 1
34 0034 1
35 0035 1
36 0036 1 ++
37 0037 1
38 0038 1 MODULE: LNK_SYMSEIRINS
39 0039 1
40 0040 1 FACILITY: LINKER
41 0041 1
42 0042 1 ABSTRACT: SYMBOL TABLE SEARCH AND INSERT
43 0043 1
44 0044 1 HISTORY:
45 0045 1
46 0046 1 VERSION: X01.00
47 0047 1
48 0048 1 AUTHOR: T.J. PORTER 18-FEB-77
49 0049 1
50 0050 1 MODIFIED BY:
51 0051 1
52 0052 1 V03-002 JWT0062 Jim Teague 22-Oct-1982
53 0053 1 Replaced symbol hashing algorithm.
54 0054 1
55 0055 1 V03-001 JWT0031 Jim Teague 25-May-1982
56 0056 1 Zero hashtable before use for module local symbols
57 0057 1

```



LNK\_SYMSEIRINS  
V04=000

E 15

16-Sep-1984 00:36:22  
14-Sep-1984 12:40:37

VAX-11 Bliss-32 V4.0-742  
[LINKER.SRC]LNKSYMTBL.B32;1

Page 2  
(1)

.. 58 0058 1 !  
.. 59 0059 1 !  
.. 60 0060 1 !  
.. 61 0061 1 !  
.. 62 0062 1 !  
.. 63 0063 1 !  
.. 64 0064 1 !  
.. 65 0065 1 !  
.. 66 0066 1 !--

V03-003 BLS0090 Benn Schreiber 31-Oct-1981  
Add LNK\$SEARCHLOCAL routine  
V03-002 BLS0025 Benn Schreiber 10-Nov-1980  
Enhancements to shareable images.  
V03-001 BLS0007 Benn Schreiber, 3-Jun-1980  
Convert to MDL data structures.

```
68 0067 1
69 0068 1 ++
70 0069 1
71 0070 1 FUNCTIONAL DESCRIPTION:
72 0071 1
73 0072 1 THIS MODULE CONTAINS THE SYMBOL TABLE SEARCH AND INSERT
74 0073 1 ROUTINES. THE SYMBOL TABLE IS A HASH
75 0074 1 TABLE USING A CHAIN OF ALTERNATES WHEN COLLISIONS OCCUR.
76 0075 1 THE TABLE CONSISTS OF SYM$C TBLSIZ CONTIGUOUS DESCRIPTORS
77 0076 1 EACH DESCRIPTOR CONTAINS A POINTER WHICH IS THE HEAD OF
78 0077 1 A SINGLY LINKED LIST, USED IF A COLLISION OCCURS ON
79 0078 1 THAT ENTRY. MULTIPLE COLLISIONS ARE INSERTED IN THIS LIST,
80 0079 1 THE LAST HAVING A ZERO POINTER.
81 0080 1 THE COLLISION LIST ENTRIES ARE ALLOCATED (BY INSERT) FROM
82 0081 1 DYNAMIC MEMORY.
83 0082 1
84 0083 1 THE CALLING SEQUENCES ARE:
85 0084 1 LNK$SEARCH (TARGSYMBOL, DESCRADR, SNBADR)
86 0085 1 LNK$INSERT (TARGSYMBOL, DESCRADR, SNBADR)
87 0086 1 LNK$SEARCHLOCAL (TARGSYMBOL, ENVINDEX, DESCRADR, SNBADR, ENVDESCADR)
88 0087 1 WHERE: TARGSYMBOL IS THE ADDRESS OF AN ASCII STRING TO
89 0088 1 BE FOUND OR INSERTED.
90 0089 1
91 0090 1 DESCRADR IS THE ADDRESS OF CELL TO STORE THE ADDRESS
92 0091 1 OF A FOUND ENTRY OR ADDRESS OF AN INSERTED ENTRY.
93 0092 1
94 0093 1 SNBADR IS THE ADDRESS OF A CELL TO STORE THE ADDRESS
95 0094 1 OF A FOUND ENTRY SYMBOL NAME BLOCK OR THE ADDRESS
96 0095 1 OF THE SYMBOL NAME BLOCK IF THE ENTRY WAS INSERTED.
97 0096 1
98 0097 1 SEARCH HAS THE VALUE TRUE IF THE SYMBOL WAS FOUND,
99 0098 1 FALSE IF NOT.
100 0099 1
101 0100 1 CALLS TO INSERT MUST BE PRECEDED BY AN UNSUCCESSFUL
102 0101 1 SEARCH CALL, IN THIS CASE INFORMATION IS
103 0102 1 RECORDED TO OBVIATE ANOTHER SEARCH AND
104 0103 1 DESCRADR IS RETURNED WITH THE ADDRESS OF THE DESCRIPTOR
105 0104 1 WHICH HAS THE STRING COPIED INTO IT.
106 0105 1
107 0106 1 HASH VALUE H = SUM OF CHARACTERS, DIVIDED BY THE TABLE SIZE.
108 0107 1
109 0108 1 --
110 0109 1
111 0110 1 LIBRARY
112 0111 1 'STARLETL32';
113 0112 1 REQUIRE
114 0113 1 'PREFIX'; ! GET GENERAL DEFINITIONS
115 0228 1 LIBRARY
116 0229 1 'DATBAS'; ! LINKER DATA STRUCTURES
117 0230 1
118 0231 1 EXTERNAL ROUTINE
119 0232 1 LNK$ALLOBLK, ! DYNAMIC MEMORY ALLOCATOR
120 0233 1 LNK$FNDENVMAP; ! FIND ENVIRONMENT MAPPING TABLE ENTRY
121 0234 1
122 0235 1 LITERAL
123 0236 1 NINE = 9,
124 0237 1 THIRTEEN = 13;
```

LNK\_SYMSEIRINS  
V04=000

6 15  
16-Sep-1984 00:36:22  
14-Sep-1984 12:40:37

VAX-11 Bliss-32 V4.0-742  
[LINKER.SRC]LNKSYMTBL.B32;1

Page 4  
(2)

```
: 125      0238 1
: 126      0239 1 EXTERNAL LITERAL
: 127      0240 1      SYMSC_ALLOBLK : BYTLIT;          ! NUMBER OF PAGES TO PREALLOCATE
: 128      0241 1
: 129      0242 1 OWN
: 130      0243 1      SYMENTRY : REF BLOCK[,BYTE];      ! CURRENT SYMBOL ENTRY
: 131      0244 1 GLOBAL
: 132      0245 1      LNK$GL_SYMALLOC : VECTOR[2, LONG], ! SIZE AND POINTER TO PREALLOCATED TABLE
: 133      0246 1      SYM$GL_HASHTBL : REF VECTOR[SYMSC_TBLSIZ, LONG]; ! THE HASH TABLE FOR SYMBOLS
```



```
135 0247 1 GLOBAL ROUTINE LNK$SEARCH (TARGSYMBOL, DESCRADR, SNBADR) =
136 0248 1
137 0249 2 BEGIN
138 0250 2
139 0251 2 TARGSYMBOL IS ADDRESS OF AN ASCII STRING
140 0252 2 DESCRADR IS ADDRESS OF CELL TO RECEIVE THE ENTRY
141 0253 2 ADDRESS IF SYMBOL IS IN TABLE
142 0254 2 SNBADR IS ADDRESS OF CELL TO RECEIVE THE SYMBOL NAME BLOCK
143 0255 2 ADDRESS IF SYMBOL IS IN TABLE
144 0256 2
145 0257 2 MAP
146 0258 2 TARGSYMBOL : REF VECTOR[.BYTE];
147 0259 2
148 0260 2 BUILTIN
149 0261 2 ROT;
150 0262 2
151 0263 2 REGISTER
152 0264 2 HASHINDEX;
153 0265 2
154 0266 2 LOCAL
155 0267 2 LEFTOVER,
156 0268 2 LONGWORDS,
157 0269 2 CH_RESULT,
158 0270 2 PREVENTRY,
159 0271 2 POINTER;
160 0272 2
161 0273 2 COMPUTE THE HASH INDEX AND GET ENTRY ADDRESS
162 0274 2
163 0275 2 HASHINDEX = .TARGSYMBOL[0]; ! INITIALIZE THE HASH VALUE
164 0276 2 LEFTOVER = .HASHINDEX AND 3;
165 0277 2 LONGWORDS = .HASHINDEX ^ -2;
166 0278 2 POINTER = TARGSYMBOL[1]; ! SET CHARACTER POINTER TO INCLUDE STRING LENGTH
167 0279 2 INCR I FROM 1 TO .LONGWORDS DO
168 0280 2 BEGIN
169 0281 2 HASHINDEX = ..POINTER XOR .HASHINDEX;
170 0282 2 POINTER = .POINTER + 4;
171 0283 2 HASHINDEX = ROT (.HASHINDEX, NINE);
172 0284 2 END;
173 0285 2 INCR I FROM 1 TO .LEFTOVER DO
174 0286 2 BEGIN
175 0287 2 HASHINDEX = CH$RCHAR A(POINTER) XOR .HASHINDEX;
176 0288 2 HASHINDEX = ROT (.HASHINDEX, THIRTEEN);
177 0289 2 END;
178 0290 2
179 0291 2 HASHINDEX = (.HASHINDEX AND ZX'7FFFFFFF') MOD SYM$C_TBL$IZ; ! THEN TAKE MODULO TABLE SIZE
180 0292 2 SYMENTRY = (SYM$GL_HASHTBL[.HASHINDEX]); ! GET ADDRESS OF HASH TABLE ENTRY
181 0293 2 IF .SYMENTRY[SNB$L_COLIST] EQL 0
182 0294 2 THEN RETURN FALSE
183 0295 2 ELSE BEGIN
184 0296 2 PREVENTRY = .SYMENTRY; ! REMEMBER PREVIOUS
185 0297 2 SYMENTRY = .SYMENTRY[SNB$L_COLIST]; ! POINT TO THE FIRST ENTRY
186 0298 2
187 0299 2
188 0300 2 NOW COMPARE THE SYMBOL IN THE
189 0301 2 ENTRY FOR A MATCH. IF IT MATCHES RETURN ENTRY
190 0302 2 ADDRESS AND SUCCESS CONDITION.
191 0303 2 IF IT DOES NOT MATCH SEARCH DOWN THE COLLISION
LIST UNTIL:
```

```
192 0304 1. FIND A MATCH - RETURN THE ADDRESS OF MATCHED
193 0305 ENTRY AND SUCCESS
194 0306 2. REACH END OF LIST. SAVE ADDRESS OF LAST
195 0307 ENTRY IN LIST FOR POSSIBLE SUBSEQUENT
196 0308 INSERT AND RETURN FAILURE.
197 0309
198 0310 DO IF (CH_RESULT = CH$COMPARE(.TARGSYMBOL[0], TARGSYMBOL[1], ! COMPARE SYMBOLS
199 0311 .SYMENTRY[SNB$B_NAMLANG], SYMENTRY[SNB$T_NAME])) EQL 0
200 0312 THEN BEGIN ! SYMBOL MATCHES
201 0313 .DESCRADR = .SYMENTRY + .SYMENTRY[SNB$B_NAMLANG] + SNB$C_FXDLEN;
202 0314 .SNBADR = .SYMENTRY; ! RETURN SYMBOL-NAME BLOCK
203 0315 ! AND VALUE BLOCK ADDRESSES
204 0316 RETURN TRUE; ! AND RETURN SUCCESS
205 0317 END
206 0318
207 0319 UNTIL (IF .CH_RESULT LSS 0 ! OTHERWISE, QUIT IF PAST THE SPOT
208 0320 THEN BEGIN ! RESET POINTER TO INSERT SPOT
209 0321 SYMENTRY = .PREVENTRY;
210 0322 TRUE
211 0323 END
212 0324 ELSE BEGIN
213 0325 PREVENTRY = .SYMENTRY; ! SAVE PREVIOUS
214 0326 IF .SYMENTRY[SNB$L_COLIST] EQL 0 ! IF AT END OF LIST
215 0327 THEN TRUE
216 0328 ELSE BEGIN
217 0329 SYMENTRY = .SYMENTRY [SNB$L_COLIST]; ! LINK TO NEXT
218 0330 FALSE
219 0331 END
220 0332 END
221 0333 );
222 0334 ! END OF THE COLLISION LIST.
223 0335 RETURN FALSE; ! THE LAST ENTRY EXAMINED
224 0336 ! IS PRESERVED IN SYMENTRY.
225 0337 END; ! END OF NON-0 HASH TABLE ENTRY
226 0338 1 END; ! END OF SEARCH ROUTINE
```

```
.TITLE LNK_SYMSEIRINS
.IDENT \V04-000\
.PSECT $OWN$,NOEXE,2
00000 SYMENTRY:
.BLKB 4
.PSECT $GLOBAL$,NOEXE,2
00000 LNK$GL_SYMMALLOC::
.BLKB 8
00008 SYM$GL_HASHTBL::
.BLKB 4
.EXTRN LNK$ALLOBLK, LNK$FNDENVMAP
.EXTRN SYM$C_ALLOBLK
.PSECT $CODE$,NOWRT,2
```



			07FC 00000	.ENTRY	LNK\$SEARCH, Save R2,R3,R4,R5,R6,R7,R8,R9,-	
		5A	00000000'	EF 9E 00002	MOVAB SYMENTRY, R10	0247
		50	04	BC 9A 00009	MOVZBL @TARGSYMBOL, HASHINDEX	0275
54	50	02		00 EF 0000D	EXTZV #0, #2, HASHINDEX, LEFTOVER	0276
	53	50	FE	8F 78 00012	ASHL #-2, HASHINDEX, LONGWORDS	0277
		57	04	AC D0 00017	MOVL TARGSYMBOL, R7	0278
		52	01	A7 9E 0001B	MOVAB 1(R7), POINTER	
				51 D4 0001F	CLRL I	0279
				07 11 00021	BRB 2\$	
		50		82 CC 00023 1\$:	XORL2 (POINTER)+, HASHINDEX	0281
	50	50		09 9C 00026	ROTL #9, HASHINDEX, HASHINDEX	0283
	F5	51		53 F3 0002A 2\$:	AOBLEQ LONGWORDS, I, 1\$	0279
				51 D4 0002E	CLRL I	0285
				0A 11 00030	BRB 4\$	
		53		82 9A 00032 3\$:	MOVZBL (POINTER)+, R3	0287
		50		53 CC 00035	XORL2 R3, HASHINDEX	
	50	50		0D 9C 00038	ROTL #13, HASHINDEX, HASHINDEX	0288
	F2	51		54 F3 0003C 4\$:	AOBLEQ LEFTOVER, I, 3\$	0285
50	50	1F		00 EF 00040	EXTZV #0, #31, HASHINDEX, HASHINDEX	0291
7E	00	50		01 7A 00045	EMUL #1, HASHINDEX, #0, -(SP)	
50	50	8E	00000115	8F 7B 0004A	EDIV #277, (SP)+, HASHINDEX, HASHINDEX	
		6A	00000000'FF	40 DE 00053	MOVAL @SYM\$GL HASHTBL[HASHINDEX], SYMENTRY	0292
		50		6A D0 0005B	MOVL SYMENTRY, R0	0293
				60 D5 0005E	TSTL (R0)	
				47 13 00060	BEQL 9\$	
		58		50 D0 00062	MOVL R0, PREVENTRY	0296
		6A		60 D0 00065	MOVL (R0), SYMENTRY	0297
		50	04	BC 9A 00068 5\$:	MOVZBL @TARGSYMBOL, R0	0310
		54		6A D0 0006C	MOVL SYMENTRY, R4	0311
		55	04	A4 9A 0006F	MOVZBL 4(R4), R5	
		56		01 D0 00073	MOVL #1, R6	
55	00	01	A7	50 2D 00076	CMPC5 R0, 1(R7), #0, R5, 5(R4)	
			05	A4 0007C		
				03 1A 0007E	BGTRU 6\$	
		56		01 D9 00080	SBWC #1, R6	
		59		56 D0 00083 6\$:	MOVL R6, CH_RESULT	
				0E 12 00086	BNEQ 7\$	
	08	BC	05 A544	9E 00088	MOVAB 5(R5)[R4], @DESCRADR	0313
	0C	BC		54 D0 0008E	MOVL R4, @SNBADR	0314
		50		01 D0 00092	MOVL #1, R0	0316
				04 00095	RET	
			05	18 00096 7\$:	BGEQ 8\$	0319
		6A		58 D0 00098	MOVL PREVENTRY, SYMENTRY	0321
				0C 11 0009B	BRB 9\$	
		58		54 D0 0009D 8\$:	MOVL R4, PREVENTRY	0325
				64 D5 000A0	TSTL (R4)	0326
				05 13 000A2	BEQL 9\$	
		6A		64 D0 000A4	MOVL (R4), SYMENTRY	0329
				BF 11 000A7	BRB 5\$	
				50 D4 000A9 9\$:	CLRL R0	0335
				04 000AB	RET	0338

; Routine Size: 172 bytes, Routine Base: \$CODE\$ + 0000

```
228 0339 1 GLOBAL ROUTINE LNK$INSERT(TARGSYMBOL, DESCRADR, SNBADR) : NOVALUE =
229 0340 2 BEGIN
230 0341 2
231 0342 2 TARGSYMBOL IS ADDRESS OF AN ASCII STRING, AN ENTRY
232 0343 2 FOR WHICH IS TO BE INSERTED IN THE SYMBOL TABLE. THE
233 0344 2 ADDRESS OF THIS ENTRY IS TO BE RETURNED IN THE CELL
234 0345 2 DESCRADR. THE ADDRESS OF THE SYMBOL NAME BLOCK IS RETURNED
235 0346 2 IN THE CELL POINTED TO BY SNBADR. THIS ROUTINE REQUIRES THAT
236 0347 2 AN UNSUCCESSFUL CALL ON SEARCH PRECEDED IT AND SAVED THE
237 0348 2 ADDRESS OF THE LAST ENTRY EXAMINED.
238 0349 2
239 0350 2 MAP
240 0351 2 TARGSYMBOL : REF VECTOR[, BYTE];
241 0352 2 LOCAL
242 0353 2 BLOCKSIZE,
243 0354 2 NEWENTRY : REF BLOCK[, BYTE];
244 0355 2
245 0356 2 BLOCKSIZE = (SYM$C_SIZE+SNB$C_FXDLEN+.TARGSYMBOL[0] + 3) AND NOT 3;
246 0357 2 IF .LNK$GL_SYMMALLOC[0] LEQU .BLOCKSIZE
247 0358 2 THEN BEGIN
248 0359 2 LNK$ALLOBLK(SYM$C_ALLOBLK*512, LNK$GL_SYMMALLOC[1]);
249 0360 2 LNK$GL_SYMMALLOC[0] = SYM$C_ALLOBLK*512;
250 0361 2 END;
251 0362 2 NEWENTRY = .LNK$GL_SYMMALLOC[1];
252 0363 2 LNK$GL_SYMMALLOC[0] = .LNK$GL_SYMMALLOC[0] - .BLOCKSIZE;
253 0364 2 LNK$GL_SYMMALLOC[1] = .LNK$GL_SYMMALLOC[1] + .BLOCKSIZE;
254 0365 2
255 0366 2
256 0367 2
257 0368 2
258 0369 2 NEWENTRY[SNB$C_COLIST] = .SYMENTRY[SNB$C_COLIST];
259 0370 2 SYMENTRY[SNB$C_COLIST] = .NEWENTRY;
260 0371 2 SYMENTRY = .NEWENTRY;
261 0372 2
262 0373 2 HAVE AN EMPTY DESCRIPTOR - COPY IN THE SYMBOL
263 0374 2 STRING
264 0375 2
265 0376 2 CH$MOVE(.TARGSYMBOL[0]+1, TARGSYMBOL[0],
266 0377 2 SYMENTRY[SNB$C_NAMLEN]);
267 0378 2 .SNBADR = .SYMENTRY;
268 0379 2 SYMENTRY = .SYMENTRY + .TARGSYMBOL[0] + SNB$C_FXDLEN;
269 0380 2 CH$FILL(0, SYM$C_SIZE, SYMENTRY);
270 0381 2 SYMENTRY[SYM$C_NAMLEN] = .TARGSYMBOL[0];
271 0382 2 .DESCRADR = .SYMENTRY;
272 0383 2 RETURN;
273 0384 1 END;
```

! ALLOCATE A BLOCK  
! WHICH CONSISTS OF  
! SYMBOL VALUE BLOCK +  
! SIZE OF NAME  
! + NAME BLOCK OVERHEAD  
! LINK INTO THE LIST  
! LINK IT ON TO COLLISION LIST  
! AND REPLACE OLD POINTER

COPY NAME  
(NO EXTRA BYTES IN NAME)  
RETURN SYMBOL NAME BLOCK ADDRESS  
POINT TO SYMBOL VALUE BLOCK  
ZERO THE ENTRY  
SET LENGTH INTO VALUE BLOCK  
RETURN ITS ADDRESS  
AND THAT'S IT  
OF INSERT ROUTINE.

52

```
59 00000000' 03FC 00000
58 00000000' EF 9E 00002
57 04 BC 9A 00010
50 2C A7 9E 00014
50 03 CB 00018
```

```
.ENTRY LNK$INSERT, Save R2,R3,R4,R5,R6,R7,R8,R9 : 0339
MOVAB LNK$GL_SYMMALLOC, R9
MOVAB SYMENTRY, R8
MOVZBL @TARGSYMBOL, R7
MOVAB 44(R7), R0
BICL3 #3, R0, BLOCKSIZE
```

0356

LNK\_SYMSEIRINS  
V04=000

L 15  
16-Sep-1984 00:36:22  
14-Sep-1984 12:40:37

VAX-11 Bliss-32 V4.0-742  
[LINKER.SRC]LNKSYMTBL.B32:1

Page 9  
(4)

		52		69	D1	0001C	CML	LNK\$GL_SYMMALLOC, BLOCKSIZE	0357	
				17	1A	0001F	BGTRU	18	0359	
			04	A9	9F	00021	PUSHAB	LNK\$GL_SYMMALLOC+4		
			00000000*	8F	DD	00024	PUSHL	#<SYMSY_ALLOBLK*512>		
		00000000G	00	77	FB	0002A	CALLS	#2, LNK\$ALLOBLK		
			69	8F	DD	00031	MOVL	#<SYMSY_ALLOBLK*512>, LNK\$GL_SYMMALLOC	0360	
			50	04	A9	DD	00038	18: MOVL	LNK\$GL_SYMMALLOC+4, NEWENTRY	0362
			69		52	C2	0003C	SUBL2	BLOCKSIZE, LNK\$GL_SYMMALLOC	0363
		04	A9		52	C0	0003F	ADDL2	BLOCKSIZE, LNK\$GL_SYMMALLOC+4	0364
			60	00	B8	DD	00043	MOVL	@SYMENTRY, (NEWENTRY)	0369
		00	B8		50	DD	00047	MOVL	NEWENTRY, @SYMENTRY	0370
			68		50	DD	0004B	MOVL	NEWENTRY, SYMENTRY	0371
			50	01	A7	9E	0004E	MOVAB	1(R7), R0	0376
			56		68	DD	00052	MOVL	SYMENTRY, R6	0377
	04	A6	04		50	28	00055	MOVCL	R0, @TARGSYMBOL, 4(R6)	
			0C		56	DD	0005B	MOVL	R6, @SNBADR	0378
			68	05	A7	9E	0005F	MOVAB	5(R7)[R6], SYMENTRY	0379
			56		68	DD	00064	MOVL	SYMENTRY, R6	0380
24		00	6E		00	2C	00067	MOVCL	#0, (SP), #0, #36, (R6)	
					66		0006C			
			0F	A6	57	90	0006D	MOVAB	R7, 15(R6)	0381
			08	BC	56	DD	00071	MOVL	R6, @DESCRADR	0382
					04	00075	RET		0384	

; Routine Size: 118 bytes, Routine Base: \$CODE\$ + 00AC



```
275 0385 1 GLOBAL ROUTINE LNK$SEARCHLOCAL (TARGSYMBOL, ENVINDEX, DESCRADR, SNBADR, ENVDESCADR) =
276 0386 1
277 0387 1 BEGIN
278 0388 1
279 0389 1     TARGSYMBOL IS ADDRESS OF AN ASCII STRING
280 0390 1     ENVINDEX IS THE ENVIRONMENT THAT SYMBOL IS FROM
281 0391 1     DESCRADR IS ADDRESS OF CELL TO RECEIVE THE ENTRY
282 0392 1     ADDRESS IF SYMBOL IS IN TABLE
283 0393 1     SNBADR IS ADDRESS OF CELL TO RECEIVE THE SYMBOL NAME BLOCK
284 0394 1     ADDRESS IF SYMBOL IS IN TABLE
285 0395 1     ENVDESCADR IS ADDRESS OF CELL TO RECEIVE THE ENVIRONMENT
286 0396 1     DESCRIPTOR BLOCK ADDRESS OR 0 IF NOT DEFINED
287 0397 1     OR REFERENCED (OPTIONAL PARAMETER)
288 0398 1
289 0399 1 MAP
290 0400 1     TARGSYMBOL : REF VECTOR[,BYTE];
291 0401 1
292 0402 1 BUILTIN
293 0403 1     NULLPARAMETER;
294 0404 1
295 0405 1 BUILTIN
296 0406 1     ROT;
297 0407 1
298 0408 1 REGISTER
299 0409 1     HASHINDEX;
300 0410 1
301 0411 1 LOCAL
302 0412 1     LONGWORDS,
303 0413 1     LEFTOVER,
304 0414 1     MAPENT : REF BLOCK[,BYTE],
305 0415 1     ENVDESC : REF BLOCK[,BYTE],
306 0416 1     ENVNODE : REF BLOCK[,BYTE],
307 0417 1     HASHTABLE : REF VECTOR[,LONG],
308 0418 1     CH_RESULT,
309 0419 1     PREVENTRY,
310 0420 1     POINTER;
311 0421 1
312 0422 1     COMPUTE THE HASH INDEX
313 0423 1
314 0424 1     HASHINDEX = .TARGSYMBOL[0];
315 0425 1     LEFTOVER = .HASHINDEX AND 3;
316 0426 1     LONGWORDS = .HASHINDEX * -2;
317 0427 1     POINTER = TARGSYMBOL[1];
318 0428 1     INCR I FROM 1 TO .LONGWORDS DO
319 0429 1         BEGIN
320 0430 1             HASHINDEX = ..POINTER XOR .HASHINDEX;
321 0431 1             POINTER = .POINTER + 4;
322 0432 1             HASHINDEX = ROT (.HASHINDEX ,NINE);
323 0433 1         END;
324 0434 1     INCR I FROM 1 TO .LEFTOVER DO
325 0435 1         BEGIN
326 0436 1             HASHINDEX = CH$RCHAR A(POINTER) XOR .HASHINDEX;
327 0437 1             HASHINDEX = ROT (.HASHINDEX, THIRTEEN);
328 0438 1         END;
329 0439 1
330 0440 1     HASHINDEX = (.HASHINDEX AND 2X'7FFFFFFF') MOD SYM$C_TBL$SZ;
331 0441 1
```

! INITIALIZE THE HASH VALUE

! SET CHARACTER POINTER TO INCLUDE STRING LENGTH

! THEN TAKE MODULO TABLE SIZE

```
0442 2 ! FIND ENVIRONMENT SYMBOL HASH TABLE
0443
0444 MAPENT = LNK$FNDENVMAP(.ENVINDEX);
0445 IF (ENVNODE = .MAPENT[PMT$PSCDES]) NEQ 0
0446 THEN BEGIN
0447     ENVDESC = .ENVNODE + NODE$C_SHORT;
0448     HASHTABLE = .ENVDESC[NVD$SYMTBL];
0449     END
0450 ELSE BEGIN
0451     HASHTABLE = .MAPENT[PMT$SYMLST];
0452     ENVDESC = 0;
0453     END;
0454 IF .HASHTABLE EQL 0
0455 THEN BEGIN
0456     LNK$ALLOBLK(SYMSC_TBL$IZ*4, HASHTABLE);      ! ALLOCATE TABLE AND
0457     CH$FILL(0, SYMSC_TBL$IZ*4, .HASHTABLE);      ! ZERO IT BEFORE USE
0458     IF .ENVNODE NEQ 0
0459     THEN ENVDESC[NVD$SYMTBL] = .HASHTABLE
0460     ELSE MAPENT[PMT$SYMLST] = .HASHTABLE;
0461     END;
0462 IF NOT NULLPARAMETER(5)
0463 THEN .ENVDESCADR = .ENVDESC;
0464 SYMENTRY = (HASHTABLE[.HASHINDEX]);              ! GET ADDRESS OF HASH TABLE ENTRY
0465 IF .SYMENTRY[SNB$COLIST] EQL 0
0466 THEN RETURN FALSE
0467 ELSE BEGIN
0468     PREVENTRY = .SYMENTRY;                        ! REMEMBER PREVIOUS
0469     SYMENTRY = .SYMENTRY[SNB$COLIST];             ! POINT TO THE FIRST ENTRY
0470
0471     NOW COMPARE THE SYMBOL IN THE
0472     ENTRY FOR A MATCH. IF IT MATCHES RETURN ENTRY
0473     ADDRESS AND SUCCESS CONDITION.
0474     IF IT DOES NOT MATCH SEARCH DOWN THE COLLISION
0475     LIST UNTIL:
0476     1. FIND A MATCH - RETURN THE ADDRESS OF MATCHED
0477        ENTRY AND SUCCESS
0478     2. REACH END OF LIST. SAVE ADDRESS OF LAST
0479        ENTRY IN LIST FOR POSSIBLE SUBSEQUENT
0480        INSERT AND RETURN FAILURE.
0481
0482 DO IF (CH_RESULT = CH$COMPARE(.TARGSYMBOL[0], TARGSYMBOL[1], ! COMPARE SYMBOLS
0483     .SYMENTRY[SNB$B_NAMLNG], SYMENTRY[SNB$T_NAME])) EQL 0
0484 THEN BEGIN
0485     .DESCRADR = .SYMENTRY + .SYMENTRY[SNB$B_NAMLNG] + SNB$C_FXDLEN; ! SYMBOL MATCHES
0486     .SNBADR = .SYMENTRY;      ! RETURN SYMBOL-NAME BLOCK
0487     ! AND VALUE BLOCK ADDRESSES
0488     RETURN TRUE;             ! AND RETURN SUCCESS
0489     END
0490
0491 UNTIL (IF .CH_RESULT LSS 0      ! OTHERWISE, QUIT IF PAST THE SPOT
0492 THEN BEGIN
0493     SYMENTRY = .PREVENTRY;      ! RESET POINTER TO INSERT SPOT
0494     TRUE
0495     END
0496 ELSE BEGIN
0497     PREVENTRY = .SYMENTRY;      ! SAVE PREVIOUS
0498     IF .SYMENTRY[SNB$COLIST] EQL 0 ! IF AT END OF LIST
```

```

389      0499  5
390      0500  6
391      0501  6
392      0502  6
393      0503  6
394      0504  6
395      0505  6
396      0506  6
397      0507  6
398      0508  6
399      0509  6
400      0510  1

RETURN FALSE;
END;

);

END

! END OF THE COLLISION LIST.
! THE LAST ENTRY EXAMINED
! IS PRESERVED IN SYMENTRY.
! END OF NON-0 HASH TABLE ENTRY

! END OF SEARCH ROUTINE
```

```

OFFC 00000
.ENTRY LNK$SEARCHLOCAL, Save R2,R3,R4,R5,R6,R7,R8,-, 0385
R9,R10,R11
MOVAB SYMENTRY, R11
MOVZBL @TARGSYMBOL, HASHINDEX 0424
EXTZV #0, #2, HASHINDEX, LEFTOVER 0425
ASHL #2, HASHINDEX, LONGWORDS 0426
MOVL TARGSYMBOL, R10 0427
MOVAB 1(R10), POINTER
CLRL I 0428
BSBB 2$
XORL2 (POINTER)+, HASHINDEX 0430
ROTL #9, HASHINDEX, HASHINDEX 0432
AOBLEQ LONGWORDS, I, 1$ 0428
CLRL I 0434
BRB 4$
MOVZBL (POINTER)+, R2 0436
XORL2 R2, HASHINDEX
ROTL #13, HASHINDEX, HASHINDEX 0437
AOBLEQ LEFTOVER, I, 3$ 0434
EXTZV #0, #31, HASHINDEX, HASHINDEX 0440
EMUL #1, HASHINDEX, #0, -(SP)
EDIV #277, (SP)+, HASHINDEX, HASHINDEX
PUSHL ENVINDEX 0444
CALLS #1, LNK$FNDENVMAP
MOVL R0, MAPENT
MOVL (MAPENT), ENVNODE 0445
BEQL 5$
MOVAB 10(R8), ENVDESC 0447
MOVL 8(ENVDESC), HASHTABLE 0448
BRB 6$
MOVL 4(MAPENT), HASHTABLE 0451
CLRL ENVDESC 0452
TSTL HASHTABLE 0454
BNEQ 8$
PUSHL SP 0456
MOVZWL #1108, -(SP)
CALLS #2, LNK$ALLOBLK
MOVC5 #0, (SP), #0, #1108, @HASHTABLE 0457
TSTL ENVNODE 0458
```



			06	13	00092	BEQL	7\$		
08	A7		6E	D0	00094	MOVL	HASHTABLE, 8(ENVDESC)	0459	
			04	11	00098	BRB	8\$		
04	A9		6E	D0	0009A	7\$: MOVL	HASHTABLE, 4(MAPENT)	0460	
	05		6C	91	0009E	8\$: CMPB	(AP), #5	0462	
			09	1F	000A1	BLSSU	9\$		
		14	AC	D5	000A3	TSTL	20(AP)		
			04	13	000A6	BEQL	9\$		
14	BC		57	D0	000A8	MOVL	ENVDESC, @ENVDESCADR	0463	
	6B		00	BE	46	9\$: MOVAL	@HASHTABLE[HASHINDEX], SYMENTRY	0464	
	50		6B	D0	000B1	MOVL	SYMENTRY, R0	0465	
			60	D5	000B4	TSTL	(R0)		
			47	13	000B6	BEQL	14\$		
	56		50	D0	000B8	MOVL	R0, PREVENTRY	0468	
	6B		60	D0	000BB	MOVL	(R0), SYMENTRY	0469	
	50		04	BC	9A	10\$: MOVZBL	@TARGSYMBOL, R0	0482	
	54		6B	D0	000C2	MOVL	SYMENTRY, R4	0483	
	55		04	A4	9A	MOVZBL	4(R4), R5		
	57		01	D0	000C9	MOVL	#1, R7		
55		00	01	AA	50	CMPC5	R0, 1(R10), #0, R5, 5(R4)		
			05	A4	000D2				
			03	1A	000D4	BGTRU	11\$		
	57		01	D9	000D6	SBWC	#1, R7		
	58		57	D0	000D9	11\$: MOVL	R7, CH_RESULT		
			0E	12	000DC	BNEQ	12\$		
0C	BC		05	A5	44	MOVAB	5(R5)[R4], @DESCRADR	0485	
10	BC		54	D0	000E4	MOVL	R4, @SNBADR	0486	
	50		01	D0	000E8	MOVL	#1, R0	0488	
				04	000EB	RET			
			05	18	000EC	12\$: BGEQ	13\$	0491	
	5B		56	D0	000EE	MOVL	PREVENTRY, SYMENTRY	0493	
			0C	11	000F1	BRB	14\$		
	56		54	D0	000F3	13\$: MOVL	R4, PREVENTRY	0497	
			64	D5	000F6	TSTL	(R4)	0498	
			05	13	000F8	BEQL	14\$		
	6B		64	D0	000FA	MOVL	(R4), SYMENTRY	0501	
			BF	11	000FD	BRB	10\$		
			50	54	000FF	14\$: CLRL	R0	0507	
				04	00101	RET		0510	

; Routine Size: 256 bytes, Routine Base: \$CODE\$ + 0122

```

: 402      0511 1 GLOBAL ROUTINE LNK$UPCASE_D (DESCR) =
: 403      0512 2 BEGIN
: 404      0513 2
: 405      0514 2 THIS ROUTINE UPCASES THE STRING DESCRIBED BY DESCR.
: 406      0515 2
: 407      0516 2 MAP
: 408      0517 2     DESCR : REF BBLOCK;
: 409      0518 2
: 410      0519 2 BIND
: 411      0520 2     BYTESTRING = .DESCR[DSC$A_POINTER] : VECTOR[,BYTE];
: 412      0521 2
: 413      0522 2 LOCAL
: 414      0523 2     CCHAR : BYTE;
: 415      0524 2
: 416      0525 2 IF .DESCR[DSC$W_LENGTH] NEQ 0
: 417      0526 2 THEN INCRU I FROM 0 TO .DESCR[DSC$W_LENGTH] - 1
: 418      0527 2     DO IF (CCHAR = .BYTESTRING[I]) GEQU %ASCII 'a'
: 419      0528 2         AND .CCHAR LEQU %ASCII 'z'
: 420      0529 2         THEN BYTESTRING[I] = .CCHAR - 32;
: 421      0530 2
: 422      0531 2 RETURN TRUE
: 423      0532 1 END;
```

			001C 00000	.ENTRY	LNK\$UPCASE_D, Save R2,R3,R4	0511
	50	04	AC D0 00002	MOVL	DESCR, R0	0520
			60 B5 00006	TSTW	(R0)	0525
			2A 13 00008	BEQL	4\$	
	54		60 3C 0000A	MOVZWL	(R0), R4	0526
			54 D7 0000D	DECL	R4	
			51 D4 0000F	CLRL	I	
			1C 11 00011	BRB	3\$	
	52	04 B041	9A 00013 1\$:	MOVZBL	@4(R0)[I], R2	0527
	53		52 90 00018	MOVB	R2, CCHAR	
61	8F		52 91 0001B	CMPB	R2, #97	
			0C 1F 0001F	BLSSU	2\$	
7A	8F		53 91 00021	CMPB	CCHAR, #122	0528
			06 1A 00025	BGTRU	2\$	
04 B041	53		20 83 00027	SUBB3	#32, CCHAR, @4(R0)[I]	0529
			51 D6 0002D 2\$:	INCL	I	0527
	54		51 D1 0002F 3\$:	CMPL	I, R4	
			DF 1B 00032	BLEQU	1\$	
	50		01 D0 00034 4\$:	MOVL	#1, R0	0531
			04 00037	RET		0532

: Routine Size: 56 bytes, Routine Base: %CODE\$ + 0224

```

: 424      0533 1 GLOBAL ROUTINE LNK$UPCASE_C (STRINGADR) =
: 425      0534 2 BEGIN
: 426      0535 2
: 427      0536 2 THIS ROUTINE UPCASES THE ASCII STRING POINTED TO BY STRINGADR
: 428      0537 2
: 429      0538 2 MAP
```

```
: 430      0539 2    STRINGADR : REF VECTOR[.BYTE];
: 431      0540 2
: 432      0541 2    LOCAL
: 433      0542 2      CCHAR : BYTE;
: 434      0543 2
: 435      0544 2    IF .STRINGADR[0] NEQ 0
: 436      0545 2    THEN INCRU I FROM 1 TO .STRINGADR[0]
: 437      0546 2      DO IF (CCHAR = .STRINGADR[I]) GEQU %ASCII 'a'
: 438      0547 2        AND .CCHAR LEQU %ASCII 'z'
: 439      0548 2      THEN STRINGADR[I] = .CCHAR - 32;
: 440      0549 2
: 441      0550 2    RETURN TRUE
: 442      0551 1    END;
```

			000C 00000	.ENTRY	LNK\$UPCASE_C, Save R2,R3	: 0533
	52	04	BC 9A 00002	MOVZBL	@STRINGADR, R2	: 0544
			26 13 00006	BEQL	4\$	
	50		01 D0 00008	MOVL	#1, I	: 0545
			1C 11 0000B	BRB	3\$	
	51	04	BC40 9A 0000D 1\$:	MOVZBL	@STRINGADR[I], R1	: 0546
	53		51 90 00012	MOVB	R1, CCHAR	
61	8F		51 91 00015	CMPB	R1, #97	
			0C 1F 00019	BLSSU	2\$	
7A	8F		53 91 0001B	CMPB	CCHAR, #122	: 0547
			06 1A 0001F	BGTRU	2\$	
04	BC40		53 20 83 00021	SUBB3	#32, CCHAR, @STRINGADR[I]	: 0548
			50 D6 00027 2\$:	INCL	I	: 0546
	52		50 D1 00029 3\$:	CMPL	I, R2	
			DF 1B 0002C	BLEQU	1\$	
	50		01 D0 0002E 4\$:	MOVL	#1, R0	: 0550
			04 00031	RET		: 0551

; Routine Size: 50 bytes, Routine Base: \$CODE\$ + 025C

; 443 0552 0 END ELUDOM

## PSECT SUMMARY

Name	Bytes	Attributes
\$OWNS	4	NOVEC, WRT, RD, NOEXE, NOSHR, LCL, REL, CON, NOPIC, ALIGN(2)
\$GLOBALS	12	NOVEC, WRT, RD, NOEXE, NOSHR, LCL, REL, CON, NOPIC, ALIGN(2)
\$CODE\$	654	NOVEC, NOWRT, RD, EXE, NOSHR, LCL, REL, CON, NOPIC, ALIGN(2)



LNK\_SYMSEIRINS  
V04=000

F 16  
16-Sep-1984 00:36:22  
14-Sep-1984 12:40:37

VAX-11 Bliss-32 V4.0-742  
[LINKER.SRC]LNKSYMTBL.B32;1

Page 16  
(6)

Library Statistics

File	----- Total	Symbols Loaded	----- Percent	Pages Mapped	Processing Time
\$255\$DUA28:[SYSLIB]STARLET.L32;1	9776	6	0	581	00:01.0
-\$255\$DUA28:[LINKER.OBJ]DATBAS.L32;1	538	11	2	28	00:00.4

COMMAND QUALIFIERS

BLISS/CHECK=(FIELD,INITIAL,OPTIMIZE)/LIS=LISS:LNKSYMTBL/OBJ=OBJ\$:LNKSYMTBL MSRC\$:LNKSYMTBL/UPDATE=(ENH\$:LNKSYMTBL)

: Size: 654 code + 16 data bytes  
: Run Time: 00:14.6  
: Elapsed Time: 00:44.9  
: Lines/CPU Min: 2266  
: Lexemes/CPU-Min: 14751  
: Memory Used: 111 pages  
: Compilation Complete



0219 AH-BT13A-SE  
VAX/VMS V4.0

DIGITAL EQUIPMENT CORPORATION  
CONFIDENTIAL AND PROPRIETARY

LNKPROIB  
LIS

LNKSYMTBL  
LIS

LNKSYMOUT  
LIS

LNKUMALLO  
LIS

LNKPSCTBL  
LIS

LNKPROSHR  
LIS

LNKSTATSO  
LIS